

### **TECHNICAL SHEET**

26/11/2025



Pneumatic V-cutting saw for 2x45° angle cutting, equipped with special blades arranged one above the other for simultaneous undercutting of the glazing bead web. The machine is equipped as standard with pneumatic, vertical special clamping device which enables the simultaneous processing of glazing beads.

- Options:
- Roller conveyor with stand
- · Stop and measuring systems
- Profile counterblocks
- Blades

### (someco)

### **TECHNICAL SHEET**

26/11/2025



## Snap-in interchangeable counterblocks

The counterblocks are very easy to change: a snap-in mechanism enables them to be changed without having to use any other tools.



### Workpiece clamping system

The workpiece is clamped from above by means of clamps; thin profiles can also be clamped by GLS 192 from the bottom to avoid the risk of deformation and to ensure a greater cutting precision.



### **Cutting module**

Glass stopper cuts are made by 2 cutting units, one set at 45° and the other at 135°. Each cutting unit is made up of 2 blades: the first actually cuts the glass stopper and the second, which has a smaller diameter, makes the cut in the glass stopper that is to house the gasket. This machine configuration enables 2 profiles to be inserted in the counterblocks so that 2 glass stoppers can be cut at the same time.



## Connection to roller conveyors and stop gauges

Beside the cutting area there is a steel support for connecting the machine to an infeed roller conveyor or a stop gauge that ensures high positioning precision while cutting the glass stopper.



### GLS 192 B / COMPLEMENTARY MACHINES

# 

The overall dimensions may vary depending on the product configuration.

WORK AREA	
Maximum cutting width (mm)	130
Maximum cutting height (mm)	44,5
Minimum profile length (mm)	240

DIMENSION AND WEIGHT	
Length (mm)	460
Depth (mm)	1.040
Height (mm)	1.120
Weight (kg)	140

MOTORS	
Three-phase asynchronous motors	2
Motors power (kW)	2 x 0,9


MODES OF OPERATION	
Vertical clamps	2
Simultaneous cutting of 2 glazing beads	•
Automatic cutting sequence	•
Operation by foot switch	•

Voilàp S.p.A. Via Archimede, 10 41019 - Limidi di Soliera (MO) ITALY

Tel 059 895411 Fax: 059 859404 P.IVA e C.F. 02057270361 info@somecopvc.com www.somecopvc.com The right to make technical alterations is reserved.



#### **CUTTING DIAGRAM**



TOOLS	
Blades type	HSS
Blade diameter (mm)	200
Blade diameter (45° beveled) (mm)	98
Blade bore (mm)	32
Blade speed - 50 Hz motor (r.p.m.)	2.800
Blade speed - 60 Hz motor (r.p.m.)	3.400

EQUIPMENT	
Vertical clamping device	•
Glazing bead counterblock	0
Roller conveyor	0
Manual measuring systems	0
Roller conveyor / measuring system connecting plate	0

1,9
16
10

PNEUMATIC CONNECTION	
Pressure (bar)	7
Hose connection	DN10
Compressed air consumption (7 bar) per working cycle (without spraying) (I)	20

### Included • Available O



Tel 059 895411 Fax: 059 859404 P.IVA e C.F. 02057270361 info@somecopvc.com www.somecopvc.com The right to make technical alterations is reserved.