




PWS 1800

Transport and trolleys




Profile trolley for vertical storage and transportation of aluminium profiles. Stable steel construction. Ideal for transportation and space-saving intermediate storage of cut-to-length profiles. Vertical profile transportation. Sufficient for 12 - 60 profile bars. Compartment divider height is adjustable. Lower supporting surface with rubber strips. Compartment dividers with protective tubing. Rear back support with rubber strips. Four castors, two of which have a fixing brake. Option: height of additional compartment divider is adjustable, with plastic protector.




Compartment divider with plastic protector

Compartment divider height is adjustable. All supporting surfaces have a non-slip PVC cladding which protects surfaces from damage during storage



Back support with rubber strips

Rear supporting surfaces equipped with rubber strips protect profiles from damage




Lower supporting surfaces with rubber strips

Lower supporting surfaces equipped with rubber strips to protect the profiles from damage



Casters

Four casters, two of which have a fixing brake, provide a high degree of mobility and easy, safe handling



Additional compartment divider (Optional)

Additional compartment divider with height adjustment and plastic protector



PWS 1800 / TRANSPORT AND TROLLEYS

CHARACTERISTICS

Length (mm)	1.880
Width (mm)	800
Height (mm)	1.700
Compartment dividers	2
Compartments	12
Swivel castors diameter (mm)	125
Compartment width (mm)	120
Compartment depth (mm)	540
Support height (mm)	1.500
Weight (kg)	105
Load capacity (kg)	350
Quantity of profile bars	12 - 60
Profile trolley with loading on one side	●
Compartment dividers with protective tubing	●
Lower supporting surface with rubber strips	●
Rear back support with rubber strips	●
Additional height adjustable compartment divider with plastic protection	○

Included ● Available ○